

| GENERAL Dower type | 0 | | Gasoline / LPG |
|--------------------------|----|-------------------------------|-------------------|
| Power type | 2 | | |
| Base capacity | 3 | | 5,000 lb |
| Load center | 4 | | 24 in |
| WEIGHTS | | | |
| Service weight | 5 | unloaded | 8,488 lb |
| Axle load | 6 | loaded / unloaded, front | 12,390 / 3,479 lb |
| | 7 | loaded / unloaded, rear | 1,610 / 5,010 lb |
| TIRES | | | |
| Tire type | 8 | | Pneumatic |
| Wheels | 9 | front / rear | 2/2 |
| Wheelbase | 10 | | 64.9 in |
| Tire size | 11 | front | 7.00-12-12 PR |
| | 12 | rear | 6.00-9-10 PR |
| Tread width | 13 | front / rear | 37.8 / 36.3 in |
| MAST | | | |
| Max. fork height | 14 | with std 2-stage mast | 118 in |
| Free lift | 15 | with std 2-stage mast | 5.7 in |
| Height, upright lowered | 16 | with std 2-stage mast | 85.6 in |
| Height, upright extended | 17 | with std 2-stage mast | 160.9 in |
| Mast tilt, fwd, back | 18 | with std 2-stage mast | 6° / 12° |
| Carriage | 19 | width | 40.9 in |
| Fork spread | 20 | minimum / maximum | 9 / 39.7 in |
| Fork dimensions | 21 | TxWxL | 1.5 x 3.9 x 42 in |
| CHASSIS | | | |
| Length to fork face | 22 | with std 2-stage mast | 99.5 in |
| Overall width | 23 | ota i otago maot | 45.2 in |
| Overhead guard height | 24 | | 85.8 in |
| Turning radius | 25 | minimum outside | 89.7 in |
| Fork overhang | 26 | with std 2-stage mast | 18.1 in |
| Right angle stack | 27 | add load length and clearance | 157.9 in |
| Ground clearance | 28 | minimum loaded | 4.7 in |
| | 29 | center of wheelbase | 5.7 in |
| | | | |

| Performance | | | |
|-------------------|----|-------------------|----------------|
| Travel speed | 30 | loaded / unloaded | 11 / 11.5 km/h |
| Lift speed | 31 | loaded / unloaded | 137 / 143 fpm |
| Lower speed | 32 | loaded / unloaded | 98 / 78.7 fpm |
| Max. drawbar pull | 33 | loaded | 3,968 lb |
| Max. gradeability | 34 | loaded / unloaded | 20 / 31 % |

| Systems | | | |
|---------|----|---------------------|-------------------------|
| Brakes | 35 | service | Foot / hyd |
| | 36 | parking | Hand / mech |
| Engine | 37 | manufacturer | Kubota |
| | 38 | model | WG2503 |
| | 39 | emission compliance | EPA certified |
| | 40 | cylinders | 4 |
| | 41 | displacement | 2.5 liter |
| | 42 | rated power | 59 hp |
| | 43 | max. torque | 128 / 1,600 lb/ft (rpm) |

