

LIUGONG

S2646E

AMP


WORKING HEIGHT
MAX.
10 M (32'1")

OVERALL LIFT
CAPACITY MAX.
450 KG (992 LB)

OVERALL WIDTH
1.19 M (3'10")




OVERALL LENGTH
2.49 M (8'2")

OVERALL WEIGHT
2,540 KG (5,599 LB)



**XTRACARE
WARRANTY**

S2646E SPECIFICATIONS >>>



DIMENSIONS

A. Working Height Max.	10 m (32'10")
B. Platform Height Max.	8 m (26'3")
C. Platform Height (Stowed)	1.22 m (4')
D. Platform Length	2.28 m (7'6")
E. Platform Width	1.15 m (3'9")
F. Extension Deck (Roll Out)	0.9 m (2'11")
G. Overall Length	2.49 m (8'2")
H. Overall Length (Without Ladder)	2.29 m (7'6")
I. Overall Width	1.19 m (3'10")
J. Stowed Height (Rails Up)	2.36 m (7'9")
K. Stowed Height (Rails Down)	1.8 m (5'10")
L. Wheelbase	1.88 m (6'2")
M. Ground Clearance (Pothole Raised)	0.1 m (4")
N. Ground Clearance (Pothole Deployed)	0.02 m (0.8")

PRODUCTIVITY

Overall Lift Capacity Max.	450 kg (992 lb)
Extension Deck Capacity	120 kg (264 lb)
Platform Occupancy Max. (Indoor/Outdoor)	2 / 1
Drive Speed (Stowed)	4 km/h (2.49 mph)
Drive Speed (Raised)	0.7 km/h (0.43 mph)
Turning Radius (Inside/Outside)	0.24 / 2.39 m (9' / 7'10")
Lift/Lower Time	43 / 35 s
Gradeability	25 %
Tilt Sensor Activation (Side to Side/Front to Back)	X 1.5° / Y 3°
Tire Size (Solid Non-marking)	381 × 127 mm (1'3" x 5")

POWER

Battery	24 V / 225 Ah
Charger	24 V / 30 A
Lift Motor	24 V / 3.3 kW
Drive Motor	24 V / 0.7 kW

WEIGHT

Overall Weight	2,540 kg (5,599 lb)
----------------	---------------------